



Circuit diagram: E0214-149

POS	ITEM No	DESCRIPTION	QTY.
1	I0695	Connector 10P UTOW	1
2	16811903-8	KRAFTKABEL 12X0,75	1
3	I0483	Adapter Shield	1
4	I1698	Straight heat shrink boot	1
5	I0603	Cable gland M25	1
6	I0302	Pin 0,5-1,0mm2	10
7	11699198-301	Tape	2

Där ej annat angivits gäller / Unless otherwise stated the following applies:		Material	Ämne / Blank
Tolerans / Tolerance:		Värme behandling / Heat treatment	
Ytjämnhet / Surface roughness:		Ytbehandling / Surface coating	
Gradningsklass enligt / Burring class acc. to:		Ritningsmött gäller efter ytbehandling. / Meas. valid after coated surfaces	
Konstruerad av / Designed by: MTh 2009-05-12		Benämning	
Ändrad av / Changed by:		Skala / Scale	
Godkänd av / Approved by:		1:2	
		Vikt / Weight	
		0 kg	
		Format	
		A2	
		Description	
		P8117	
		Dokument nr. / Document no.	
		P8117	
		Filnamn / Filename	
		A0214-149A	
		Ändr. / Alt.	
		B	
		Blad / Sheet	
		1(1)	

We reserve rights in this document and in the information contained therein. Reproduction or distribution of this document without express authority is strictly forbidden. Robot System Products