

Circuit diagram: E0214-204



POS	ITEM No	DESCRIPTION	QTY.
1	10695	Connector 10P UTOW	1
2	16811903-8	KRAFTKABEL 12X0,75	1
3	10483	Adapter Shield	1
4	11698	Straight heat shrink boot	1
5	10302	Pin 0,5-1,0mm2	10
6	11699198-301	Tape	1

Article	L=
P8146-40	4000mm

Där ej annat angivits gäller / Unless otherwise stated the following applies:		Material	Ämne / Blank
Tolerans / Tolerance:		Värme behandling / Heat treatment	
Ytjämnhet / Surface roughness:		Ytbehandling / Surface coating	
Gradningsklass enligt / Burring class acc. to:		Ritningsmätt gäller efter ytbehandl. / Meas. valid after coated surfaces	
Konstruerad av / Designed by: MTh 2012-08-27		Benämning	
Ändrad av / Changed by:		Signal cable 10P- Free end	
Godkänd av / Approved by:		Skala / Scale: 1:2	Description: P8146
		Vikt / Weight: 0,2 kg	Finamn / Filename: A0214-204A
		Format: A2	Dokument nr. / Document no.: P8146
			Ändr. / Alt.: B
			Blad / Sheet: 1(1)



We reserve rights in this document and in the information contained therein. Reproduction or distribution of this document without express authority is strictly forbidden. Robot System Products